

Parametry pomp ZPG w zależności od konfiguracji

Typ pompy	Wydajność [m ³ /h]	Wysokość podnoszenia [m]	Średnica zanieczyszczeń [mm]	Moc pompy [kW]	Prąd nominalny [A]	Napięcie zasilania [V]	Masa [kg]
ZPG-80-H-K-(D,R)-P	0-100	70-30	10	15,5	22/11	500/1000	215
ZPG-80-N-K-(D,R)-P	0-130	53-25	30,20	16	23/11,5	500/1000	215
ZPG-80-N-KS-M-P	0-130	53-25	20	16	23/11,5	500/1000	225
ZPG-80-N-S-(D,R)-P	0-130	53-25	35	16	23/11,5	500/1000	220
ZPG-80-L-S-(D,M)-P	0-(50-100)	(35-20)-0	40	16	23/11,5	500/1000	220
ZPG-80-L-K-(D,R)-P	0-(50-100)	(35-20)-0	30	16	23/11,5	500/1000	220
ZPG-80-L-KS-M-P	0-(50-100)	(35-20)-0	30	16	23/11,5	500/1000	225
ZPG-65-N-K-(D,R)-P	0-80	44-5	20	10	14/7	500/1000	190
ZPG-65-N-KS-M-P	0-80	44-5	20	10	14/7	500/1000	200
ZPG-65-N-S-(D,R)-P	0-80	44-5	20	10	14/7	500/1000	190
ZPG-65-L-K-(D,R)-P	0-(50-100)	(35-20)-0	20	14	20/10	500/1000	190
ZPG-65-L-KS-M-P	0-(50-100)	(35-20)-0	20	14	20/10	500/1000	200
ZPG-65-L-S-(D,M)-P	0-(50-100)	(35-20)-0	40	14	20/10	500/1000	190